

3 Pin Surface Mount Schottky Diodes

Search:

Device	Device Marking	V R (V)	I F (mA)	VF Max(V)	VF I F (mA)	IR Max(μA)	IR V R (V)	Style	Package	PDF Datasheet
WSD706F	3J	40	30	0.37	0.001	1	10	A	SOT-323	datasheet
BAT54A	B6	30	200	0.4	10	2	25	B	SOT-23	datasheet
BAT54AW	B7	30	200	0.4	10	2	25	B	SOT-323	datasheet
BAT54C	5C	30	200	0.4	10	2	25	A	SOT-23	datasheet
BAT54CW	5C	30	200	0.4	10	2	25	A	SOT-323	datasheet
BAT54	JV3	30	200	0.4	10	2	25	E	SOT-23	datasheet
BAT54S	LD3	30	200	0.4	10	2	25	C	SOT-23	datasheet
BAT54SW	B8	30	200	0.4	10	2	25	C	SOT-323	datasheet
BAT54W	B4	30	200	0.4	10	2	25	E	SOT-323	datasheet

Device	Device Marking	V R (V)	I F (mA)	VF Max(V)	VF I F (mA)	IR Max(μA)	IR V R (V)	Style	Package	PDF Datasheet
WSD715F	3D	40	30	0.37	1	1	10	A	SOT-323	datasheet
BAS40-04	CB	40	120	0.56	10	1	30	C	SOT-23	datasheet
BAS40-05	45	40	120	0.56	10	1	30	A	SOT-23	datasheet
BAS40-06	L2	40	120	0.56	10	1	30	B	SOT-23	datasheet
BAS40	B1	40	120	0.56	10	1	30	E	SOT-23	datasheet
BAS70-04	CG	70	70	0.75	10	0.1	50	C	SOT-23	datasheet
BAS70-05	EH	70	70	0.41	1	0.1	50	A	SOT-23	datasheet
BAS70-06	GK	70	70	0.75	10	0.1	50	B	SOT-23	datasheet
BAS70	BE	70	70	0.75	10	0.1	50	E	SOT-23	datasheet